



## Dual-port 32Gb Gen 6 Fibre Channel expansion card with SFP+ transceivers

Standard Warranty	3 years
PCIe and Lanes	PCIe Gen3 x8
Transmission rates	Fibre Channel 32/16/8 Gb/s (Up to 28.05 Gb/s per port)
Form factor	Low-profile PCIe card 10.68 x 6.89 cm (4.20 x 2.71 inches)
Supported NAS operating system	QTS 4.4.1 / QuTS hero 4.5.0 (or later) for QNAP NAS with PCIe slots as a FC Target. <a href="#">Check Compatible NAS Models</a>
Bracket	Low-profile bracket pre-installed; full-height and specialized (for selected QNAP NAS) brackets are bundled
Port and cable	32Gb Transceiver* (bundled with 2 x <a href="#">TRX-32GFCSFP-SR</a> short wavelength SFP+ transceivers) and Fibre LC Cable (optional purchase)
Operating Temperature	0°C to 45°C (32°F to 113°F)
Storage temperature	-20°C to 70°C (-4°F to 158°F)
Relative humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Note	<p>*Only QNAP certified transceivers are supported. Check <a href="#">compatibility list</a>.</p> <p>Note: QNAP Fibre Channel cards can only be installed in a QNAP NAS (with the QTS or QuTS hero operating system) as a Fibre Channel Target. Windows®, Linux®, and other systems are not supported.</p>

Note: QNAP reserves the right to replace partial parts or accessories if the original is no longer available from its manufacturer/supplier. Any replacement would be fully tested and verified to meet strict compatibility and stability guidelines and will deliver identical performance to the original.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.